

## Serie DPWQ40200



### ■ Anwendung

Self-calibrating sensor with microprocessor control for measuring carbon dioxide concentration in the air within the range from 0 to 2,000 million<sup>-1</sup> (parts per million).

### ■ Design

CO<sub>2</sub> sensor has 2 analogue outputs: 0-10 V and 4-20 mA. An analogue output provides for stepless fan speed control (requires an EC motor fan or an additional fan speed controller with input 0 ... 10 V,

for example, VFED). With stepless control the fan speed is changed in proportion to carbon dioxide concentration changes. The CO<sub>2</sub> dioxide concentration in the air is measured by means of a non-dispersive infrared analyser (NDIR).

### ■ Mounting

The sensor is mounted onto a wall or a mounting box inside the serviced space. The unit is powered from a 24 V AC/DC low-current electric mains.

### Technical data

Parameters	Values
Power source	24 V AC/DC
Gas analyser	optical (NDIR)
CO <sub>2</sub> measurement range	0-2,000 million <sup>-1</sup> (parts per million) of CO <sub>2</sub>
CO <sub>2</sub> output signal	0-10 V
CO <sub>2</sub> measurement precision	± 30 million <sup>-1</sup> (parts per million), ± 5 % of maximum value
Operating conditions	0-50 °C; 10-90 % relative humidity without condensate
Protection class	IP55
Dimensions [mm]	95x97x30